

Coast Guard, DOT

§ 15.610

or ballast control operator (BCO) authorizes service only on MODUs. A license or endorsement as OIM is restricted to the MODU type and mode of operation specified on the license.

(d) A self-propelled MODU other than a drillship must be under the command of an individual who holds a license as master endorsed as OIM.

(e) A drillship must be under the command of an individual who holds a license as master. When a drillship is on location, the individual in command must hold a license as master endorsed as OIM.

(f) A non-self-propelled MODU must be under the command of an individual who holds a license or endorsement as OIM.

(g) An individual serving as mate on a self-propelled surface unit other than a drillship must hold an appropriate license as mate and an endorsement as BS or BCO. An individual holding a license or endorsement as barge supervisor or ballast control operator may be substituted for a required mate when a self-propelled surface unit other than a drillship is on location or under tow, under certain circumstances as determined by the cognizant OCMI.

(h) An individual holding a license or endorsement as barge supervisor is required on a non-self-propelled surface unit other than a drillship.

(i) An individual holding a license or endorsement as barge supervisor may serve as ballast control operator.

(j) The OCMI issuing the MODU's certificate of inspection may authorize the substitution of chief or assistant engineer (MODU) for chief or assistant engineer, respectively, on self-propelled or propulsion assisted surface units, except drillships. The OCMI may also authorize the substitution of assistant engineer (MODU) for assistant engineer on drillships.

(k) Requirements in this part concerning radar observers do not apply to non-self-propelled MODUs.

(l) A surface mobile offshore drilling unit underway or on location, when afloat and equipped with a ballast control room, must have that ballast control room manned by an individual holding a license or endorsement au-

thorizing service as ballast control operator.

[CGD 81-059a, 55 FR 14805, Apr. 18, 1990]

§ 15.525 Reference to other parts.

Parts 31 and 35 of this chapter contain additional manning requirements applicable to tank vessels.

Subpart E—Manning Requirements; Uninspected Vessels

§ 15.601 General.

The following sections of subparts F, G, and H of this part contain provisions concerning manning of uninspected vessels; §§ 15.701, 15.705, 15.710, 15.720, 15.730, 15.801, 15.805, 15.810, 15.820, 15.825, 15.840, 15.850, 15.855, 15.905, 15.910, and 15.915.

§ 15.605 Licensed operators for uninspected passenger vessels.

Each self-propelled, uninspected vessel carrying not more than six passengers, as defined by 46 U.S.C. 2101(21)(D), must be under the direction and control of an individual licensed by the Coast Guard.

§ 15.610 Master and mate (pilot) of towing vessels.

Every towing vessel at least 8 meters (at least 26 feet) in length measured from end to end over the deck (excluding sheer), except a vessel described by the next sentence, must be under the direction and control of a person licensed as master or mate (pilot) of towing vessels or as master or mate of vessels of appropriate gross tonnage holding an endorsement on his or her license for towing vessels. This does not apply to any vessel engaged in assistance towing, or to any towing vessel of less than 200 gross tons engaged in the offshore mineral and oil industry if the vessel has sites or equipment of that industry as its place of departure or ultimate destination.

[USCG-1999-6224, 64 FR 63235, Nov. 19, 1999]

EFFECTIVE DATE NOTE: By USCG-1999-6224, 64 FR 63235, Nov. 19, 1999, § 15.610 was revised, effective Nov. 20, 2000. For the convenience of the user, the superseded text is set forth as follows: